



MERLIN DIESEL SYSTEMS LTD

Bradkirk Place, Walton Summit Centre
Preston, Lancashire
England, PR5 8AJ

T: +44 (0)1772 694190

F: +44 (0)1772 314545

E: equip@merlindiesel.com

W: www.merlindiesel.com

TEST EQUIPMENT DIVISION

S400-5 INJECTOR TESTER

SPECIFICATIONS

| | |
|--------------------|--|
| PRESSURE RANGE: | 0-700 Bar, psi, MPa or kgf/cm ² |
| TIME RANGE: | 0-99.9 seconds |
| PRESSURE: | ±1 bar |
| TIMING: | ±1 second |
| TRANSDUCER: | ±0.1% of full value |
| LINEARITY: | ±1 bar over full range |
| MEMORY: | Data store/recall for injector type test plans |
| DISPLAY: | LED, Tick/cross symbols advise user of NOP and back-leak pass/fail |
| COMPENSATION: | Automatic compensation for variations in test oil temperature |
| CALIBRATION FLUID: | Shell Calibration Fluid 4113, now S9365 |
| DIMENSIONS | |
| HEIGHT: | 770mm |
| LENGTH: | 600mm |
| WIDTH: | 600mm |
| WEIGHT: | 66kg |

S400-5 INJECTOR TESTER

