



## MERLIN DIESEL SYSTEMS LTD

Bradkirk Place, Walton Summit Centre  
Preston, Lancashire  
England, PR5 8AJ

T: +44 (0)1772 694190

F: +44 (0)1772 314545

E: [equip@merlindiesel.com](mailto:equip@merlindiesel.com)

W: [www.merlindiesel.com](http://www.merlindiesel.com)

### TEST EQUIPMENT DIVISION

#### S425A INJECTOR TESTER

#### SPECIFICATIONS

PRESSURERANGE:	0-700 bar, psi, MPa or kgf/cm <sup>2</sup>
TIME RANGE:	0-99.9 seconds
PRESSURE:	±1 bar
TIMING:	±1 second
TRANSDUCER:	±0.1% of full value
LINEARITY:	±1 bar over full range
MEMORY:	Data store/recall for injector type test plans
DISPLAY:	LED, Tick/cross symbols advise user of NOP and back-leak pass/fail
COMPENSATION:	Automatic compensation for variations in test oil temperature
CALIBRATIONFLUID:	Shell Calibration Fluid 4113, now S9365
<b>Dimensions</b>	
HEIGHT:	770mm
LENGTH:	600mm
WIDTH:	650mm
WEIGHT:	66kg
<b>Installation details</b>	
ELECTRICAL SUPPLY	240v/1 phase/50Hz
	110v/1 phase/60Hz



S425 INJECTOR TESTER